



Beneficiary Travel

Technical Manual

Version 1.0

April 2002

Department of Veterans Affairs
VISTA Software Design & Development

Table of Contents

Introduction.....	1
Orientation.....	3
General Information.....	5
Namespace and Conventions	5
Integrity Checker.....	5
SACC Exemptions/Non-Standard Code	5
Implementation and Maintenance.....	7
Parameter Rates Enter/Edit	7
Routines.....	9
Routine to Map.....	9
Callable Routines	9
Routine List.....	9
Files.....	11
Globals and Files.....	11
File List	11
Templates.....	11
Exported Options	13
Menu Diagrams.....	13
Exported Protocols	13
Exported Options	13
Exported List Templates	13
Archiving and Purging	15
External/Internal Relations	17
DBIA Agreements.....	17
Package Wide-Variables	19
VADPT Variables (See Appendix).....	19
VAUTOMA	19
How to Generate On-Line Documentation.....	21
Security	23
Security Keys	23
FileMan Access Codes.....	23
Glossary.....	25
Appendix - VADPT Variables	27
Overview	27
Supported References	28
Callable Entry Points in VADPT.....	29
Alpha Subscripts	65

Introduction

There are no major changes in this version from PIMS V. 5.3. The purpose of this version is to create Beneficiary Travel into its own namespace (DGBT) separate from the Registration package (DG).

The Beneficiary Travel options provide the ability to perform the functions involved in issuing beneficiary travel pay. Travel reimbursement is provided to specified categories of eligible veterans. Issuance of travel pay to the veterans in some of these categories is subject to a deductible per visit and per month. The deduction requirement may be waived for any veteran who meets specific criteria subject to the approval of the local medical center director or designee. Some of the categories have income limitations. An income certification form is completed and signed yearly by the veteran. Cash reimbursement is paid on VAF 70-3542d, Voucher for Cash Reimbursement of Beneficiary Travel Expenses.

Non-employee attendants who are eligible for travel reimbursement will be issued travel pay under the veteran's name in the computer.

Payment for travel by special mode (ambulance, hired car, handicapped van, etc.) may be authorized if medically necessary and approved BEFORE travel begins. Exception to this would be in cases of medical emergency where delay would be hazardous to life or health.

For claims with an account type of ALL OTHER, the system will compute the amount payable from factors such as account type, parameter set up of deductible amount per visit and per month, one-way or round-trip mileage, and applied costs. The amount payable for claims with an account type of C&P will also be computed by the system.

Orientation

This is the technical manual for the Beneficiary Travel software package. It is designed to provide necessary information for use in the technical operation of the Beneficiary Travel software product. The technical manual is intended for use by technical computer personnel and not the typical end user.

General Information

Namespace and Conventions

The namespace assigned to Beneficiary Travel is DGBT.

Integrity Checker

Beneficiary Travel uses KIDS integrity checker. Under the installation option of the Kernel Installation Distribution System menu, select Verify Checksums in Transport Global to ensure that the routines are correct.

SACC Exemptions/Non-Standard Code

There are no SACC exemptions/non-standard code in the Beneficiary Travel package.

Implementation and Maintenance

The Beneficiary Travel package may be tailored specifically to meet the needs of the various sites. The Beneficiary Travel package will function around the parameters defined through the Parameter Rates Enter/Edit option.

Parameter Rates Enter/Edit

The Parameter Rates Enter/Edit option is used to establish site specific parameters for the Beneficiary Travel package. You must hold the DGBT SUPERVISOR key to access this option.

Listed below is a brief explanation of each site parameter.

BT CERTIFYING OFFICIAL

This is the name of the official which will appear on all VA Forms 70-3542d, Cash Reimbursement of Beneficiary Travel Expenses. If this field is left blank, the user's name will be printed followed by DESIGNEE OF CERTIFYING OFFICIAL.

BT OTHER EXPENSES ASKED

This field is used to determine if the MEALS & LODGING and FERRY, BRIDGES, ETC. prompts will be asked in the Beneficiary Travel Claim Enter/Edit option. YES or NO.

EFFECTIVE DATE

New travel rates are determined each fiscal year. The rates should be entered each year with the effective date of Oct 1. Changing values for the current or past fiscal year could result in changes to claims already entered.

DEDUCTIBLE AMOUNT/VISIT

This is the deductible amount to be applied per visit.

DEDUCTIBLE AMOUNT/MONTH

This is the monthly maximum deductible amount.

MILEAGE RATE

This is the amount of travel pay paid per mile.

FISCAL SYMBOLS

These are the fiscal symbols for beneficiary travel for the selected fiscal year. May be left blank if so desired.

C&P REVIEW VISIT MILEAGE RATE

This is the amount of travel pay paid per mile for compensation and pension examination review visits.

Parameter Rates Enter/Edit

Example

BT CERTIFYING OFFICIAL: **GREGOR,PETER** MAS
BT OTHER EXPENSES ASKED: **YES**

New travel rates are determined each fiscal year. The rates should be entered each year with the effective date of Oct 1.

Changing values for the current or past fiscal years could result in changes to the claims already entered.

Select EFFECTIVE DATE: **10/1/01** OCT 01, 2001

Are you adding 'OCT 01, 2001' as a new MAS EVENT RATES (the 11TH)? No// **YES**
(Yes)

ENTER DEDUCTIBLE AMOUNT/VISIT: **6**

ENTER DEDUCTIBLE AMOUNT/MONTH: **18**

MILEAGE RATE: **.11**

C&P REVIEW VISIT MILEAGE RATE: **.1**

FISCAL SYMBOLS: **361021222.330**

Routines

Routines to Map

There are no Beneficiary Travel routines recommended for mapping.

Callable Routines

VADATE	Generic Date Routine
VADPT	Obtain Patient Information
VALM	List Manager
VAUTOMA	Generic One, Many, All Routine

See Package-Wide Variables section of this manual for entry points.

Routine List

The following are the steps you may take to obtain a listing of the routines contained in the Beneficiary Travel package.

- 1) Programmer Options Menu
- 2) Routine Tools Menu
- 3) First Line Routine Print Option
- 4) Routine Selector: DGBT*

Files

Globals and Files

The main global used in the Beneficiary Travel package is ^DGBT. Journaling of the ^DGBT global is mandatory.

The MAS EVENT RATE file and MAS PARAMETERS file belong to the Registration package and contain fields granting ownership to the Beneficiary Travel package.

File List

<u>FILE NUMBER</u>	<u>FILE NAME</u>	<u>GLOBAL</u>
43	MAS PARAMETERS Field BT CERTIFYING OFFICIAL BT OTHER EXPENSES ASKED USE TEMPORARY ADDRESS	^DG(43, Field # (#720) (#721) (#722)
43.1	MAS EVENT RATES Field DEDUCTIBLE/VISIT DEDUCTIBLE/MONTH MILEAGE RATE FISCAL SYMBOLS C&P REVIEW VISIT MILEAGE RATE	^DG(43.1, Field # (#30.01) (#30.02) (#30.03) (#30.04) (#30.05)
392	BENEFICIARY TRAVEL CLAIM	^DGBT(392,
392.1	BENEFICIARY TRAVEL DISTANCE	^DGBT(392.1,
392.2	BENEFICIARY TRAVEL CERTIFICATION	^DGBT(392.2,
392.3	BENEFICIARY TRAVEL ACCOUNT	^DGBT(392.3,
392.4	BENEFICIARY TRAVEL MODE OF TRANSPORTATION	^DGBT(392.4,

Templates

- 1) VA FileMan Menu
- 2) Print File Entries Option
- 3) Output from what File: Print Template, Sort Template, Input Template, List Template
- 4) Sort by: Name
- 5) Start with name: DGBT to DGBTZ
- 6) Within name, sort by: <RET>
- 7) First print field: Name

Exported Options

The following are the steps you may take to obtain information about menus, exported protocols, exported options, and exported list templates concerning the Beneficiary Travel package.

Menu Diagrams

1. Programmers Options
2. Menu Management
3. Display Menus and Options Menu
4. Diagram Menus
5. Select User or Option Name: O.DGBT BENE TRAVEL MENU

Exported Protocols

1. VA FileMan Menu
2. Print File Entries Option
3. Output from what File: PROTOCOL
4. Sort by: Name
5. Start with name: DGBT to DGBTZ
6. Within name, sort by: <RET>
7. First print field: Name

Exported Options

1. VA FileMan Menu
2. Print File Entries Option
3. Output from what File: OPTION
4. Sort by: Name
5. Start with name: DGBT to DGBTZ
6. Within name, sort by: <RET>
7. First print field: Name

Exported List Templates

1. VA FileMan Menu
2. Print File Entries Option
3. Output from what File: LIST TEMPLATES
4. Sort by: Name
5. Start with name: DGBT to DGBTZ
6. Within name, sort by: <RET>
7. First print field: Name

Archiving and Purging

There are no archiving and purging capabilities connected to the Beneficiary Travel package.

External/Internal Relations

Minimums of VA FileMan V. 21.0, Kernel V. 8.0, and PIMS V. 5.3 are required to run this package.

DBIA AGREEMENTS

The following are the steps you may take to obtain the database integration agreements for the Beneficiary Travel package.

DBIA Agreements - Custodial Package

1. FORUM
2. DBA Menu
3. Integration Agreements Menu
4. Custodial Package Menu
5. Active by Custodial Package Option
6. Select Package Name: Beneficiary Travel

DBIA Agreements - Subscriber Package

1. FORUM
2. DBA Menu
3. Integration Agreements Menu
4. Subscriber Package Menu
5. Print Active by Subscriber Package Option
6. Start with subscriber package: Beneficiary Travel

Package-Wide Variables

There are no package-wide variables associated with the Beneficiary Travel package.

VADPT Variables

See Appendix.

VAUTOMA

VAUTOMA is a routine which will do a one/many/all prompt - returning the chosen values in a subscripted variable specified by the calling programmer.

Input variables:

VAUTSTR	string which describes what is to be entered.
VAUTNI	defines if array is sorted alphabetically or numerically.
VAUTVB	name of the subscripted variable to be returned.
VAUTNALL	define this variable if you do not want the user to be given the ALL option.

Other variables as required by a call to ^DIC (see VA FileMan Programmers Manual).

Output variables:

As defined in VAUTVB

How To Generate On-Line Documentation

This section describes some of the various methods by which users may secure Beneficiary Travel technical documentation. On-line technical documentation pertaining to the Beneficiary Travel software, in addition to that which is located in the help prompts and on the help screens which are found throughout the Beneficiary Travel package, may be generated through utilization of several KERNEL options. These include but are not limited to: XINDEX, Menu Management Inquire Option File, Print Option File, and FileMan List File Attributes.

Entering question marks at the "Select ... Option:" prompt may also provide users with valuable technical information. For example, a single question mark (?) lists all options which can be accessed from the current option. Entering two question marks (??) lists all options accessible from the current one, showing the formal name and lock for each. Three question marks (???) displays a brief description for each option in a menu while an option name preceded by a question mark (?OPTION) shows extended help, if available, for that option.

For a more exhaustive option listing and further information about other utilities which supply on-line technical information, please consult the **VISTA** Kernel Reference Manual.

XIndex

This option analyzes the structure of a routine(s) to determine in part if the routine(s) adheres to **VISTA** Programming Standards. The XINDEX output may include the following components: compiled list of errors and warnings, routine listing, local variables, global variables, naked globals, label references, and external references. By running XINDEX for a specified set of routines, the user is afforded the opportunity to discover any deviations from **VISTA** Programming Standards which exist in the selected routine(s) and to see how routines interact with one another, that is, which routines call or are called by other routines.

To run XINDEX for the Beneficiary Travel package, specify the following namespaces at the "routine(s) ?>" prompt: DGBT*.

Beneficiary Travel initialization routines which reside in the UCI in which XINDEX is being run, compiled template routines, and local routines found within the Beneficiary Travel namespace should be omitted at the "routine(s) ?>" prompt. To omit routines from selection, preface the namespace with a minus sign (-).

List File Attributes

This FileMan option allows the user to generate documentation pertaining to files and file structure. Utilization of this option via the "Standard" format will yield the following data dictionary information for a specified file(s): file name and description, identifiers, cross-references, files pointed to by the file specified, files which point to the file specified, input templates, print templates, and sort templates. In addition, the following applicable data is supplied for each field in the file: field name, number, title, global location, description, help prompt, cross-reference(s), input transform, date last edited, and notes.

Using the "Global Map" format of this option generates an output which lists all cross-references for the file selected, global location of each field in the file, input templates, print templates, and sort templates.

Security

Security Keys

The following are the steps you may take to obtain information about the security keys contained in the Beneficiary Travel package.

1. VA FileMan Menu
2. Print File Entries Option
3. Output from what File: SECURITY KEY
4. Sort by: Name
5. Start with name: DGBT to DGBTZ
6. Within name, sort by: <RET>
7. First print field: Name
8. Then print field: Description

FileMan Access Codes

Below is a list of recommended FileMan Access Codes associated with each file contained in the Beneficiary Travel package. This list may be used to assist in assigning users appropriate FileMan Access Codes.

<u>FILE NUMBER</u>	<u>FILE NAME</u>	<u>DD ACCESS</u>	<u>RD ACCESS</u>	<u>WR ACCESS</u>	<u>DEL ACCESS</u>	<u>LAYGO ACCESS</u>
43**	MAS PARAMETERS	@	d	D	@	@
43.1**	MAS EVENT RATES	@	d	D	D	D
392	BENEFICIARY TRAVEL CLAIM	@	d	@	@	@
392.1	BENEFICIARY TRAVEL DISTANCE	@	d	D	D	D
392.2	BENEFICIARY TRAVEL CERTIFICATION	@	d	D	D	D
392.3	BENEFICIARY TRAVEL ACCOUNT	@	d	@	@	@
392.4	BENEFICIARY TRAVEL MODE OF TRANSPORTATION	@	d	D	@	D

** Files owned by the Registration package contain fields belonging to the Beneficiary Travel package.

Glossary

C&P	Compensation & Pension
KIDS	Kernel Installation and Distribution System
MAS	Medical Administration Service
PIMS	Patient Information Management System
SACC	Standards and Conventions Committee
VISTA	Veterans Health Information Systems and Technology Architecture

Appendix – VADPT Variables

I. OVERVIEW

VADPT is a utility routine designed to provide a central point where a programmer can obtain information concerning a patient's record. Supported entry points are provided which will return demographics, inpatient status, eligibility information, etc.

Access to patient information is not limited to using the supported entry points in VADPT. Integration agreements can be established through the DBA between PIMS and other packages to reference information. Additionally, several data elements are supported without an integration agreement.

II. SUPPORTED REFERENCES

The following references to patient information (PATIENT file #2) are supported **without** an integration agreement. All nationally distributed cross-references on these fields are also supported.

Field Name	Field #	Global Location	Type of Access
NAME	(#.01)	0;1	Read
SEX	(#.02)	0;2	Read
DATE OF BIRTH	(#.03)	0;3	Read
AGE	(#.033)	N/A	Read
MARITAL STATUS	(#.05)	0;5	Read
RACE	(#.06)	0;6	Read
OCCUPATION	(#.07)	0;7	Read
RELIGIOUS PREFERENCE	(#.08)	0;8	Read
DUPLICATE STATUS	(#.081)	0;18	
PATIENT MERGED TO	(#.082)	0;19	
CHECK FOR DUPLICATE	(#.083)	0;20	
SOCIAL SECURITY NUMBER	(#.09)	0;9	Read
REMARKS	(#.091)	0;10	Read
PLACE OF BIRTH [CITY]	(#.092)	0;11	Read
PLACE OF BIRTH [STATE]	(#.093)	0;12	Read
WHO ENTERED PATIENT	(#.096)	0;15	Read
DATE ENTERED INTO FILE	(#.097)	0;16	Read
WARD LOCATION	(#.1)	.1;1	Read
ROOM -BED	(#.101)	.101;1	Read
CURRENT MOVEMENT	(#.102)	.102;1	Read
TREATING SPECIALTY	(#.103)	.103;1	Read
PROVIDER	(#.104)	.104;1	Read
ATTENDING PHYSICIAN	(#.1041)	.1041;1	Read
CURRENT ADMISSION	(#.105)	.105;1	Read
LAST DMMS EPISODE NUMBER	(#.106)	.106;1	Read
LODGER WARD LOCATION	(#.107)	.107;1	Read
CURRENT ROOM	(#.108)	.108;1	Read
CURRENT MEANS TEST STATUS	(#.14)	0;14	Read
DATE OF DEATH	(#.351)	.35;1	Read
DEATH ENTERED BY	(#.352)	.35;2	Read
PRIMARY LONG ID	(#.363)	.36;3	
PRIMARY SHORT ID	(#.364)	.36;4	
CURRENT PC PRACTITIONER	(#404.01)	PC;1	Read
CURRENT PC TEAM	(#404.02)	PC;2	Read
LAST MEANS TEST	(#999.2)	N/A	Read

III. CALLABLE ENTRY POINTS IN VADPT

1. DEM^VADPT

This entry point returns demographic information for a patient.

Input:	DFN	This required variable is the internal entry number in the PATIENT file.
	VAPTYP	This optional variable can be set to the internal number of a patient eligibility. The variable can be used to indicate the patient's type such as VA, DOD, or IHS through the eligibility. If this variable is not defined or the eligibility does not exist, the VA patient IDs will be returned.
	VAHOW	This optional variable can be set to a requested format for the output array. If this variable is not defined or does not contain one of the following values, the output array will be returned with numeric subscripts. 1 -- return the output array with alpha subscripts - see alpha subscripts section (e.g., VADM(1) would be VADM("NM")) 2 -- return the output in the ^UTILITY global with numeric subscripts (e.g., ^UTILITY("VADM",\$J,1)) 12 -- return the output in the ^UTILITY global with alpha subscripts (e.g., ^UTILITY("VADM",\$J,"NM"))
	VAROOT	This optional variable can be set to a local variable or global name in which to return the output. (e.g., VAROOT="DGDEM")
Output:	VADM(1)	The NAME of the patient. (e.g., SMITH,JOHN R.)

VADM(2)	The SOCIAL SECURITY NUMBER of the patient in internal^external format. (e.g., 123456789^123-45-6789)
VADM(3)	The DATE OF BIRTH of the patient in internal^external format. (e.g., 2551025^OCT 25,1955)
VADM(4)	The AGE of the patient as of today, unless a date of death exists, in which case the age returned will be as of that date. (e.g., 36)
VADM(5)	The SEX of the patient in internal^external format. (e.g., M^MALE)
VADM(6)	The DATE OF DEATH of the patient, should one exist, in internal^external format. (e.g., 2881101.08^NOV 1,1988@08:00)
VADM(7)	Any REMARKS concerning this patient which may be on file. (e.g., Need to obtain dependent info.)
VADM(8)	The RACE of the patient in internal^external format. (e.g., 1^WHITE, NON-HISPANIC)
VADM(9)	The RELIGION of the patient in internal^external format. (e.g., 99^CATHOLIC)
VADM(10)	The MARITAL STATUS of the patient in internal^external format. (e.g., 1^MARRIED)
VA("PID")	The PRIMARY LONG ID for a patient. The format of this variable will depend on the type of patient if VAPTYP is set. (e.g., 123-45-6789)

VA("BID")	The PRIMARY SHORT ID for a patient. The format of this variable will depend on the type of patient if VAPTYP is set. (e.g., 6789)
VAERR	The error flag will have one of the following values. 0 -- no errors encountered 1 -- error encountered - DFN or ^DPT(DFN,0) is not defined

2. ELIG^VADPT

This entry point returns eligibility information for a patient.

Input:	DFN	This required variable is the internal entry number in the PATIENT file.
	VAHOW	This optional variable can be set to a requested format for the output array. If this variable is not defined or does not contain one of the following values, the output array will be returned with numeric subscripts. 1 -- return the output array with alpha subscripts - see alpha subscripts section (e.g., VAEL(1) would be VAEL("EL")) 2 -- return the output in the ^UTILITY global with numeric subscripts (e.g., ^UTILITY("VAEL",\$J,1)) 12 -- return the output in the ^UTILITY global with alpha subscripts (e.g., ^UTILITY("VAEL",\$J,"EL"))
	VAROOT	This optional variable can be set to a local variable or global name in which to return the output. (e.g., VAROOT="DGELG")

Output:	VAEL(1)	The PRIMARY ELIGIBILITY CODE of the patient in internal^external format. (e.g., 1^SERVICE CONNECTED 50-100%)
	VAEL(1,#)	An array of other PATIENT ELIGIBILITIES to which the patient is entitled to care, in internal^external format. The # sign represents the internal entry number of the eligibility in the ELIGIBILITY CODE file. (e.g., 13^PRISONER OF WAR)
	VAEL(2)	The PERIOD OF SERVICE of the patient in internal^external format. (e.g., 19^WORLD WAR I)
	VAEL(3)	If the SERVICE CONNECTED? field is YES, a "1" will be returned in the first piece; otherwise, a "0" will be returned. If service connected, the SERVICE CONNECTED PERCENTAGE field will be returned in the second piece. (e.g., 1^70)
	VAEL(4)	If the VETERAN (Y/N)? field is YES, a "1" will be returned; otherwise, a "0" will be returned. (e.g., 1)
	VAEL(5)	If an INELIGIBLE DATE exists, a "0" will be returned indicating the patient is ineligible; otherwise, a "1" will be returned. (e.g., 0)
	VAEL(5,1)	If ineligible, the INELIGIBLE DATE of the patient in internal^external format. (e.g., 2880101^JAN 1,1988)
	VAEL(5,2)	If ineligible, the INELIGIBLE TWX SOURCE in internal^external format. (e.g., 2^REGIONAL OFFICE)

VAEL(5,3)	If ineligible, the INELIGIBLE TWX CITY. (e.g., ALBANY)
VAEL(5,4)	If ineligible, the INELIGIBLE TWX STATE from which the ineligible notification was received in internal^external format. (e.g., 36^NEW YORK)
VAEL(5,5)	If ineligible, the INELIGIBLE VARO DECISION. (e.g., UNABLE TO VERIFY)
VAEL(5,6)	If ineligible, the INELIGIBLE REASON. (e.g., NO DD214)
VAEL(6)	The TYPE of patient in internal^external format. (e.g., 1^SC VETERAN)
VAEL(7)	The CLAIM NUMBER of the patient. (e.g., 123456789)
VAEL(8)	The current ELIGIBILITY STATUS of the patient in internal^external format. (e.g., V^VERIFIED)
VAEL(9)	The CURRENT MEANS TEST STATUS of the patient CODE^NAME. (e.g., A^CATEGORY A)
VAERR	The error flag will have one of the following values. 0 -- no errors encountered 1 -- error encountered - DFN or ^DPT(DFN,0) is not defined

3. MB^VADPT

This entry point returns monetary benefit information for a patient.

Input:	DFN	This required variable is the internal entry number in the PATIENT file.
--------	-----	--

	VAHOW	<p>This optional variable can be set to a requested format for the output array. If this variable is not defined or does not contain one of the following values, the output array will be returned with numeric subscripts.</p> <p>1 -- return the output array with alpha subscripts - see alpha subscripts section (e.g., VAMB(1) would be VAMB("AA"))</p> <p>2 -- return the output in the ^UTILITY global with numeric subscripts (e.g., ^UTILITY("VAMB",\$J,1))</p> <p>12 -- return the output in the ^UTILITY global with alpha subscripts (e.g., ^UTILITY("VAMB",\$J,"AA"))</p>
	VAROOT	<p>This optional variable can be set to a local variable or global name in which to return the output.</p> <p>(e.g., VAROOT="DGMB")</p>
Output:	VAMB(1)	<p>If the RECEIVING A&A BENEFITS? field is YES, a "1" will be returned in the first piece; otherwise, a "0" will be returned. If receiving A&A benefits, the TOTAL ANNUAL VA CHECK AMOUNT will be returned in the second piece. (e.g., 1^1000)</p>
	VAMB(2)	<p>If the RECEIVING HOUSEBOUND BENEFITS? field is YES, a "1" will be returned in the first piece; otherwise, a "0" will be returned. If receiving housebound benefits, the TOTAL ANNUAL VA CHECK AMOUNT will be returned in the second piece.</p> <p>(e.g., 1^0)</p>

- VAMB(3) If the RECEIVING SOCIAL SECURITY field is YES, a "1" will be returned in the first piece; otherwise, a "0" will be returned. If receiving social security, the AMOUNT OF SOCIAL SECURITY will be returned in the second piece. (e.g., 0)
- VAMB(4) If the RECEIVING A VA PENSION? field is YES, a "1" will be returned in the first piece; otherwise, a "0" will be returned. If receiving a VA pension, the TOTAL ANNUAL VA CHECK AMOUNT will be returned in the second piece. (e.g., 1^563.23)
- VAMB(5) If the RECEIVING MILITARY RETIREMENT? field is YES, a "1" will be returned in the first piece; otherwise, a "0" will be returned. If receiving military retirement, the AMOUNT OF MILITARY RETIRE-MENT will be returned in the second piece. (e.g., 0)
- VAMB(6) The RECEIVING SUP. SECURITY (SSI) field is being eliminated. Since v5.2, a "0" is returned for this variable.
- VAMB(7) If the RECEIVING VA DISABILITY? field is YES, a "1" will be returned in the first piece; otherwise, a "0" will be returned. If receiving VA disability, the TOTAL ANNUAL VA CHECK AMOUNT will be returned in the second piece. (e.g., 0)

VAMB(8)	<p>If the TYPE OF OTHER RETIREMENT field is filled in, a "1" will be returned in the first piece; otherwise, a "0" will be returned. If receiving other retirement, the AMOUNT OF OTHER RETIREMENT will be returned in the second piece.</p> <p>(e.g., 1^2500.12)</p>
VAMB(9)	<p>If the GI INSURANCE POLICY? field is YES, a "1" will be returned in the first piece; otherwise, a "0" will be returned. If receiving GI insurance, the AMOUNT OF GI INSURANCE will be returned in the second piece.</p> <p>(e.g., 1^100000)</p>
VAERR	<p>The error flag will have one of the following values.</p> <p>0 -- no errors encountered</p> <p>1 -- error encountered - DFN or ^DPT(DFN,0) is not defined</p>

4. SVC^VADPT

This entry point returns service information for a patient.

Input:	DFN	This required variable is the internal entry number in the PATIENT file.
--------	-----	--

	VAHOW	<p>This optional variable can be set to a requested format for the output array. If this variable is not defined or does not contain one of the following values, the output array will be returned with numeric subscripts.</p> <p>1 -- return the output array with alpha subscripts - see alpha subscripts section (e.g., VASV(1) would be VASV("VN"))</p> <p>2 -- return the output in the ^UTILITY global with numeric subscripts (e.g., ^UTILITY("VASV",\$J,1))</p> <p>12 -- return the output in the ^UTILITY global with alpha subscripts (e.g., ^UTILITY("VASV",\$J,"VN"))</p>
	VAROOT	<p>This optional variable can be set to a local variable or global name in which to return the output.</p> <p>(e.g., VAROOT="DGSVC")</p>
Output:	VASV(1)	<p>If the VIETNAM SERVICE INDICATED field is YES, a "1" will be returned; otherwise a "0" will be returned. (e.g., 0)</p>
	VASV(1,1)	<p>If Vietnam Service, the VIETNAM FROM DATE in internal^external format. (e.g., 2680110^JAN 10,1968)</p>
	VASV(1,2)	<p>If Vietnam Service, the VIETNAM TO DATE in internal^external format. (e.g., 2690315^MAR 15,1969)</p>
	VASV(2)	<p>If the AGENT ORANGE EXPOS. INDICATED field is YES, a "1" will be returned; otherwise a "0" will be returned. (e.g., 0)</p>

- VASV(2,1) If Agent Orange exposure, the AGENT ORANGE REGISTRATION DATE in internal^external format.
(e.g., 2870513^MAY 13,1987)
- VASV(2,2) If Agent Orange exposure, the AGENT ORANGE EXAMINATION DATE in internal^external format.
(e.g., 2871101^NOV 1,1987)
- VASV(2,3) If Agent Orange exposure, AGENT ORANGE REPORTED TO C.O. date in internal^external format.
(e.g., 2871225^DEC 25,1987)
- VASV(2,4) If Agent Orange exposure, AGENT ORANGE REGISTRATION #.
(e.g., 123456)
- VASV(2,5) If Agent Orange exposure, the AGENT ORANGE EXPOSURE LOCATION in internal^external format
(e.g., V^VIETNAM)
- VASV(3) If the RADIATION EXPOSURE INDICATED field is YES, a "1" will be returned; otherwise a "0" will be returned
(e.g., 0)
- VASV(3,1) If Radiation Exposure, RADIATION REGISTRATION DATE in internal^external format.
(e.g., 2800202^FEB 02,1980)
- VASV(3,2) If Radiation Exposure, RADIATION EXPOSURE METHOD in internal^external format.
(e.g., T^NUCLEAR TESTING)
- VASV(4) If the POW STATUS INDICATED field is YES, a "1" will be returned; otherwise a "0" will be returned.
(e.g., 0)

VASV(4,1)	If POW status, POW FROM DATE in internal^external format. (e.g., 2450319^MAR 19,1945)
VASV(4,2)	If POW status, POW TO DATE in internal^external format. (e.g., 2470101^JAN 1,1947)
VASV(4,3)	If POW status, POW CONFINEMENT LOCATION in internal^external format. (e.g., 2^WORLD WAR II - EUROPE)
VASV(5)	If the COMBAT SERVICE INDICATED field is YES, a "1" will be returned; otherwise a "0" will be returned. (e.g., 0)
VASV(5,1)	If combat service, COMBAT FROM DATE in internal^external format. (e.g., 2430101^JAN 1,1943)
VASV(5,2)	If combat service, COMBAT TO DATE in internal^external format. (e.g., 2470101^JAN 1,1947)
VASV(5,3)	If combat service, COMBAT SERVICE LOCATION in internal^external format. (e.g., 2^WORLD WAR II - EUROPE)
VASV(6)	If a SERVICE BRANCH [LAST] field is indicated, a "1" will be returned in the first piece; otherwise a "0" will be returned. (e.g., 0)
VASV(6,1)	If service branch, BRANCH OF SERVICE field in internal^external format. (e.g., 3^AIR FORCE)
VASV(6,2)	If service branch, SERVICE NUMBER field in internal^external format. (e.g., 123456789)

VASV(6,3)	If service branch, SERVICE DISCHARGE TYPE in internal^external format. (e.g., 1^HONORABLE)
VASV(6,4)	If service branch, SERVICE ENTRY DATE in internal^external format. (e.g., 2440609^JUN 9,1944)
VASV(6,5)	If service branch, SERVICE SEPARATION DATE in internal^external format. (e.g., 2480101^JAN 1,1948)
VASV(7)	If a SERVICE SECOND EPISODE field is indicated, a "1" will be returned; otherwise a "0" will be returned. (e.g., 0)
VASV(7,1)	If second episode, BRANCH OF SERVICE field in internal^external format. (e.g., 3^AIR FORCE)
VASV(7,2)	If second episode, SERVICE NUMBER field in internal^external format. (e.g., 123456789)
VASV(7,3)	If second episode, SERVICE DISCHARGE TYPE in internal^external format. (e.g., 1^HONORABLE)
VASV(7,4)	If second episode, SERVICE ENTRY DATE in internal^external format. (e.g., 2440609^JUN 9,1944)
VASV(7,5)	If second episode, SERVICE SEPARATION DATE in internal^external format. (e.g., 2480101^JAN 1,1948)
VASV(8)	If a SERVICE THIRD EPISODE field is indicated, a "1" will be returned; otherwise a "0" will be returned. (e.g., 0)

VASV(8,1)	If third episode, BRANCH OF SERVICE field in internal^external format. (e.g., 3^AIR FORCE)
VASV(8,2)	If third episode, SERVICE NUMBER field in internal^external format. (e.g., 123456789)
VASV(8,3)	If third episode, SERVICE DISCHARGE TYPE in internal^external format. (e.g., 1^HONORABLE)
VASV(8,4)	If third episode, SERVICE ENTRY DATE in internal^external format. (e.g., 2440609^JUN 9,1944)
VASV(8,5)	If third episode, SERVICE SEPARATION DATE in internal^external format. (e.g., 2480101^JAN 1,1948)
VASV(9)	If the CURRENT PH INDICATOR field is YES, a “1” will be returned; otherwise a “0” will be returned (e.g., 0)
VASV(9,1)	If the CURRENT PH INDICATOR field is YES, CURRENT PURPLE HEART STATUS in internal^external format.(e.g., 2^IN PROCESS)
VASV(9,2)	If the CURRENT PH INDICATOR field is NO, CURRENT PURPLE HEART REMARKS in internal^external format. (e.g., 5^VAMC)
VAERR	The error flag will have one of the following values. 0 -- no errors encountered 1 -- error encountered - DFN or ^DPT(DFN,0) is not defined

5. ADD^VADPT

This entry point returns address data for a patient. If a temporary address is in effect, the data returned will be that pertaining to that temporary address; otherwise, the permanent patient address information will be returned.

Input:	DFN	This required variable is the internal entry number in the PATIENT file.
	VAHOW	This optional variable can be set to a requested format for the output array. If this variable is not defined or does not contain one of the following values, the output array will be returned with numeric subscripts. 1 -- return the output array with alpha subscripts - see alpha subscripts section (e.g., VAPA(1) would be VAPA("L1")) 2 -- return the output in the ^UTILITY global with numeric subscripts (e.g., ^UTILITY("VAPA", \$J,1)) 12 -- return the output in the ^UTILITY global with alpha subscripts (e.g., ^UTILITY("VAPA", \$J, "L1"))
	VAROOT	This optional variable can be set to a local variable or global name in which to return the output. (e.g., VAROOT="DGADD")
	VAPA("P")	This optional variable can be set to force the return of the patient's permanent address. The permanent address array will be returned regardless of whether or not a temporary address is in effect. (e.g., VAPA("P")="")

VATEST("ADD",9) This optional variable can be defined to a beginning date in VA File-Manager format. If the entire range specified is not within the effective time window of the temporary address start and stop dates, the patient's regular address is returned. (e.g., VATEST("ADD",9)=2920101)

VATEST("ADD",10) This optional variable can be defined to a ending date in VA FileManager format. If the entire range specified is not within the effective time window of the temporary address start and stop dates, the patient's regular address is returned. (e.g., VATEST("ADD",10)=2920301)

Output:	VAPA(1)	The first line of the STREET ADDRESS. (e.g., 123 South Main Street)
	VAPA(2)	The second line of the STREET ADDRESS. (e.g., Apartment #1245.)
	VAPA(3)	The third line of the STREET ADDRESS. (e.g., P.O. Box 1234)
	VAPA(4)	The CITY corresponding to the street address previously indicated. (e.g., ALBANY)
	VAPA(5)	The STATE corresponding to the city previously indicated in internal^external format. (e.g., 6^CALIFORNIA)
	VAPA(6)	The ZIP CODE of the city previously indicated. (e.g., 12345)
	VAPA(7)	The COUNTY in which the patient is residing in internal^external format. (e.g., 1^ALAMEDA)

VAPA(8)	The PHONE NUMBER of the location in which the patient is currently residing. (e.g., (123) 456-7890)
VAPA(9)	If the address information provided pertains to a temporary address, the TEMPORARY ADDRESS START DATE in internal^external format. (e.g., 2880515^MAY 15,1988)
VAPA(10)	If the address information provided pertains to a temporary address, the TEMPORARY ADDRESS END DATE in internal^external format. (e.g., 2880515^MAY 15,1988)
VAPA(11)	The ZIP+4 (5 or 9 digit zip code) of the city previously indicated in internal^external format. (e.g., 123454444^12345-4444)
VAERR	The error flag will have one of the following values. 0 -- no errors encountered 1 -- error encountered - DFN or ^DPT(DFN,0) is not defined

6. OAD^VADPT

This entry point returns other specific address information.

Input:	DFN	This required variable is the internal entry number in the PATIENT file.
	VAHOW	<p>This optional variable can be set to a requested format for the output array. If this variable is not defined or does not contain one of the following values, the output array will be returned with numeric subscripts.</p> <p>1 -- return the output array with alpha subscripts - see alpha subscripts section (e.g., VAOA(1) would be VAOA("L1"))</p> <p>2 -- return the output in the ^UTILITY global with numeric subscripts (e.g., ^UTILITY("VAOA",\$J,1))</p> <p>12 -- return the output in the ^UTILITY global with alpha subscripts (e.g., ^UTILITY("VAOA,\$J","L1"))</p>
	VAROOT	<p>This optional variable can be set to a local variable or global name in which to return the output.</p> <p>(e.g., VAROOT="DGOA")</p>

VAOA("A") This optional variable may be passed to indicate which specific address the programmer wants returned. If it is not defined, the PRIMARY NEXT-OF-KIN will be returned. Otherwise, the following will be returned based on information desired.

VAOA("A")=1 primary emergency contact
 VAOA("A")=2 designee for personal effects
 VAOA("A")=3 secondary next-of-kin
 VAOA("A")=4 secondary emergency contact
 VAOA("A")=5 patient employer
 VAOA("A")=6 spouse's employer

Output:

VAOA(1) The first line of the STREET ADDRESS.
 (e.g., 123 South First Street)

VAOA(2) The second line of the STREET ADDRESS. (e.g., Apartment 9D)

VAOA(3) The third line of the STREET ADDRESS. (e.g., P.O. Box 1234)

VAOA(4) The CITY in which the contact/ employer resides.
 (e.g., NEWINGTON)

VAOA(5) The STATE in which the contact/ employer resides in internal^external format.
 (e.g., 6^CALIFORNIA)

VAOA(6) The ZIP CODE of the location in which the contact/employer resides.
 (e.g., 12345)

VAOA(7)	The COUNTY in which the contact/ employer resides in internal^external format. (e.g., 1^ALAMEDA)
VAOA(8)	The PHONE NUMBER of the contact/employer. (e.g., (415) 967-1234)
VAOA(9)	The NAME of the contact or, in case of employment, the employer to whom this address information applies. (e.g., SMITH,ROBERT P.)
VAOA(10)	The RELATIONSHIP of the contact (if applicable) to the patient; otherwise, null. (e.g., FATHER)
VAOA(11)	The ZIP+4 (5 or 9 digit zip code) of the location in which the contact/employer resides in internal^external format. (e.g., 123454444^12345-4444)
VAERR	The error flag will have one of the following values. 0 -- no errors encountered 1 -- error encountered - DFN or ^DPT(DFN,0) is not defined

7. INP^VADPT

This entry point will return data related to an inpatient episode.

Input:	DFN	This required variable is the internal entry number in the PATIENT file.
--------	-----	--

	VAHOW	<p>This optional variable can be set to a requested format for the output array. If this variable is not defined or does not contain one of the following values, the output array will be returned with numeric subscripts.</p> <p>1 -- return the output array with alpha subscripts - see alpha subscripts section (e.g., VAIN(1) would be VAIN("AN"))</p> <p>2 -- return the output in the ^UTILITY global with numeric subscripts (e.g., ^UTILITY("VAIN",\$J,1))</p> <p>12 -- return the output in the ^UTILITY global with alpha subscripts (e.g., ^UTILITY("VAIN",\$J,"AN"))</p>
	VAROOT	<p>This optional variable can be set to a local variable or global name in which to return the output.</p> <p>(e.g., VAROOT="DGIN")</p>
	VAINDT	<p>This optional variable may be set to a past date/time for which the programmer wishes to know the patient's inpatient status. This must be passed as an internal VA FileManager date/time format. If time is not passed, it will assume anytime during that day. If this variable is not defined, it will assume now as the date/time. (e.g., 2880101.08)</p>
Output:	VAIN(1)	<p>The INTERNAL NUMBER [IFN] of the admission if one was found for the date/time requested. If no inpatient episode was found for the date/time passed, then all variables in the VAIN array will be returned as null.</p> <p>(e.g., 123044)</p>

VAIN(2)	The PRIMARY CARE PHYSICIAN [PROVIDER] assigned to the patient at the date/time requested in internal^external format. (e.g., 3^SMITH,JOSEPH L.)
VAIN(3)	The TREATING SPECIALTY assigned to the patient at the date/time requested in internal^external format. (e.g., 19^GERIATRICS)
VAIN(4)	The WARD LOCATION to which the patient was assigned at the date/time requested in internal^external format. (e.g., 27^IBSICU)
VAIN(5)	The ROOM-BED to which the patient was assigned at the date/time requested in external format. (e.g., 123-B)
VAIN(6)	This will return a "1" in the first piece if the patient is in a bed status; otherwise, a "0" will be returned. A non-bed status is made based on the last transfer type to a non-bed status, (i.e., authorized absence, unauthorized absence, etc.) The second piece will contain the name of the last transfer type should one exist. (e.g., 1^FROM AUTHORIZED ABSENCE)
VAIN(7)	The ADMISSION DATE/TIME for the patient in internal^external format. (e.g., 2870213.0915^FEB 13,1987@09:15)
VAIN(8)	The ADMISSION TYPE for the patient in internal^external format. (e.g., 3^DIRECT)

VAIN(9)	The ADMITTING DIAGNOSIS for the patient. (e.g., PSYCHOSIS)
VAIN(10)	The internal entry number of the PTF record corresponding to this admission. (e.g., 2032)
VAIN(11)	The ATTENDING PHYSICIAN in internal^external format. (e.g., 25^SMITH,JOHN)
VAERR	The error flag will have one of the following values. 0 -- no errors encountered 1 -- error encountered - DFN or ^DPT(DFN,0) is not defined

8. IN5^VADPT

This entry point will return data related to an inpatient episode.

Input:	DFN	This required variable is the internal entry number in the PATIENT file.
	VAHOW	This optional variable can be set to a requested format for the output array. If this variable is not defined or does not contain one of the following values, the output array will be returned with numeric subscripts. 1 -- return the output array with alpha subscripts - see alpha subscripts section (e.g., VAIP(1) would be VAIP("MN")) 2 -- return the output in the ^UTILITY global with numeric subscripts (e.g., ^UTILITY("VAIP",\$J,1)) 12 -- return the output in the ^UTILITY global with alpha subscripts (e.g., ^UTILITY("VAIP",\$J,"MN"))

VAROOT	This optional variable can be set to a local variable or global name in which to return the output. (e.g., VAROOT="DGI5")
VAIP("D")	<p>This optional variable can be defined as follows.</p> <p>VAIP("D")=VA FileManager date in internal format. If the patient was an inpatient at the date/time passed, movement data pertaining to that date/time will be returned.</p> <p>VAIP("D")="LAST" Movement data pertaining to the last movement on file, regardless if patient is a current inpatient.</p> <p>VAIP("D")=valid date without time Will return movement data if patient was an inpatient at any time during the day on the date that was passed in.</p> <p>VAIP("D") - not passed Will return movement data if the patient was in inpatient based on "now".</p>
VAIP("L")	This optional variable, when passed, will include lodgers movements in the data. (e.g., VAIP("L")="")
VAIP("V")	Can be defined as the variable used instead of VAIP(. (e.g., VAIP("V")="SD")
VAIP("E")	This optional variable is defined as the internal file number of a specific movement. If this is defined, VAIP("D") is ignored. (e.g., VAIP("E")=123445)

VAIP("M") This optional variable can be passed as a "1" or a "0" (or null).

VAIP("M")=0 - The array returned will be based on the admission movement associated with the movement date/time passed.

VAIP("M")=1 - The array returned will be based on the last movement associated with the date/time passed.

Output:	VAIP(1)	The INTERNAL FILE NUMBER [IFN] of the movement found for the specified date/time. (e.g., 231009)
	VAIP(2)	<p>The TRANSACTION TYPE of the movement in internal^external format where:</p> <p style="margin-left: 40px;">1=admission 2=transfer 3=discharge 4=check-in lodger 5=check-out lodger 6=specialty transfer</p> <p>(e.g., 3^DISCHARGE)</p>
	VAIP(3)	The MOVEMENT DATE/TIME in internal^external date format. (e.g., 2880305.09^MAR 5,1988@09:00)
	VAIP(4)	The TYPE OF MOVEMENT in internal^external format. (e.g., 4^INTERWARD TRANSFER)
	VAIP(5)	The WARD LOCATION to which patient was assigned with that movement in internal^external format. (e.g., 32^1B-SURG)
	VAIP(6)	The ROOM-BED to which the patient was assigned with that movement in internal^external format. (e.g., 88^201-01)

VAIP(7)	The PRIMARY CARE PHYSICIAN assigned to the patient in internal^external format. (e.g., 3^SMITH,JACOB)
VAIP(8)	The TREATING SPECIALTY assigned with that movement in internal^external format. (e.g., 98^OPTOMETRY)
VAIP(9)	The DIAGNOSIS assigned with that movement. (e.g., UPPER GI BLEEDING)
VAIP(10)	This will return a "1" in the first piece if the patient is in a bed status; otherwise, a "0" will be returned. A non-bed status is made based on the last transfer type, if one exists, and a transfer to a non-bed status, (i.e., authorized absence, unauthorized absence, etc.) The second piece will contain the name of the last transfer type should one exist. (e.g., 1^FROM AUTHORIZED ABSENCE)
VAIP(11)	If patient is in an absence status on the movement date/time, this will return the EXPECTED RETURN DATE from absence in internal^external format. (e.g., 2880911^SEP 11,1988)
VAIP(12)	The internal entry number of the PTF record corresponding to this admission. (e.g., 2032)
VAIP(13)	The INTERNAL FILE NUMBER of the admission associated with this movement. (e.g., 200312)
VAIP(13,1)	The MOVEMENT DATE/TIME in internal^external format. (e.g., 2881116.08^NOV 16,1988@08:00)

VAIP(13,2)	The TRANSACTION TYPE in internal^external format. (e.g., 1^ADMISSION)
VAIP(13,3)	The MOVEMENT TYPE in internal^external format. (e.g., 15^DIRECT)
VAIP(13,4)	The WARD LOCATION associated with this patient with this movement in internal^external format. (e.g., 5^7BSCI)
VAIP(13,5)	The PRIMARY CARE PHYSICIAN assigned to the patient for this movement in internal^external format. (e.g., 16^JONES, CHARLES C)
VAIP(13,6)	The TREATING SPECIALTY for the patient for this movement in internal^external format. (e.g., 3^NEUROLOGY)
VAIP(14)	The INTERNAL FILE NUMBER of the last movement associated with this movement. (e.g., 187612)
VAIP(14,1)	The MOVEMENT DATE/TIME in internal^external format. (e.g., 2881116.08^NOV 16,1988@08:00)
VAIP(14,2)	The TRANSACTION TYPE in internal^external format. (e.g., 2^TRANSFER)
VAIP(14,3)	The MOVEMENT TYPE in internal^external format. (e.g., 4^INTERWARD TRANSFER)
VAIP(14,4)	The WARD LOCATION associated with this patient with this movement in internal^external format. (e.g., 5^7BSCI)

VAIP(14,5)	The PRIMARY CARE PHYSICIAN assigned to the patient for this movement in internal^external format. (e.g., 16^JONES, CHARLES C)
VAIP(14,6)	The TREATING SPECIALTY for the patient for this movement in internal^external format. (e.g., 3^NEUROLOGY)
VAIP(15)	The INTERNAL FILE NUMBER of the movement which occurred immediately prior to this one, if one exists. (e.g., 153201)
VAIP(15,1)	The MOVEMENT DATE/TIME in internal^external format. (e.g., 2881116.08^NOV 16,1988@08:00)
VAIP(15,2)	The TRANSACTION TYPE in internal^external format. (e.g., 2^TRANSFER)
VAIP(15,3)	The MOVEMENT TYPE in internal^external format. (e.g., 4^INTERWARD TRANSFER)
VAIP(15,4)	The WARD LOCATION associated with this patient with this movement in internal^external format. (e.g., 5^7BSCI)
VAIP(15,5)	The PRIMARY CARE PHYSICIAN assigned to the patient for this movement in internal^external format. (e.g., 16^JONES, CHARLES C)
VAIP(15,6)	The TREATING SPECIALTY for the patient for this movement in internal^external format. (e.g., 3^NEUROLOGY)

VAIP(16)	The INTERNAL FILE NUMBER of the movement which occurred immediately following this one, if one exists. (e.g., 146609)
VAIP(16,1)	The MOVEMENT DATE/TIME in internal^external format. (e.g., 2881116.08^NOV 16,1988@08:00)
VAIP(16,2)	The TRANSACTION TYPE in internal^external format. (e.g., 2^TRANSFER)
VAIP(16,3)	The MOVEMENT TYPE in internal^external format. (e.g., 4^INTERWARD TRANSFER)
VAIP(16,4)	The WARD LOCATION associated with this patient with this movement in internal^external format. (e.g., 5^7BSCI)
VAIP(16,5)	The PRIMARY CARE PHYSICIAN assigned to the patient for this movement in internal^external format. (e.g., 16^JONES, CHARLES C)
VAIP(16,6)	The TREATING SPECIALTY for the patient for this movement in internal^external format. (e.g., 3^NEUROLOGY)
VAIP(17)	The INTERNAL FILE NUMBER of the discharge associated with this movement. (e.g., 1902212)
VAIP(17,1)	The MOVEMENT DATE/TIME in internal^external format. (e.g., 2881116.08^NOV 16,1988@08:00)
VAIP(17,2)	The TRANSACTION TYPE in internal^external format. (e.g., 3^DISCHARGE)

VAIP(17,3)	The MOVEMENT TYPE in internal^external format. (e.g., 16^REGULAR)
VAIP(17,4)	The WARD LOCATION associated with this patient for this movement in internal^external format. (e.g., 5^7BSCI)
VAIP(17,5)	The PRIMARY CARE PHYSICIAN assigned to the patient for this movement in internal^external format. (e.g., 16^JONES, CHARLES C)
VAIP(17,6)	The TREATING SPECIALTY for the patient for this movement in internal^external format. (e.g., 3^NEUROLOGY)
VAIP(18)	The ATTENDING PHYSICIAN assigned to the patient for this movement in internal^external format. (e.g., 25^SMITH,JOHN)
VAERR	The error flag will have one of the following values. 0 -- no errors encountered 1 -- error encountered - DFN or ^DPT(DFN,0) is not defined

9. OPD^VADPT

Returns other pertinent patient data which is commonly used but not contained in any other calls to VADPT.

Input:	DFN	This required variable is the internal entry number in the PATIENT file.
--------	-----	--

VAHOW	<p>This optional variable can be set to a requested format for the output array. If this variable is not defined or does not contain one of the following values, the output array will be returned with numeric subscripts.</p> <p>1 -- return the output array with alpha subscripts - see alpha subscripts section (e.g., VAPD(1) would be VAPD("BC"))</p> <p>2 -- return the output in the ^UTILITY global with numeric subscripts (e.g., ^UTILITY("VAPD",\$J,1))</p> <p>12 -- return the output in the ^UTILITY global with alpha subscripts (e.g., ^UTILITY("VAPD",\$J,"BC"))</p>
VAROOT	<p>This optional variable can be set to a local variable or global name in which to return the output.</p> <p>(e.g., VAROOT="DGPD")</p>

Output:	VAPD(1)	The PLACE OF BIRTH [CITY]. (e.g., SAN FRANCISCO)
	VAPD(2)	The PLACE OF BIRTH [STATE] in internal^external format. (e.g., 6^CALIFORNIA)
	VAPD(3)	The FATHER'S NAME. (e.g., SMITH,FRED Z.)
	VAPD(4)	The MOTHER'S NAME. (e.g., MARY)
	VAPD(5)	The MOTHER'S MAIDEN NAME. (e.g., JONES,MARGARET)
	VAPD(6)	The patient's OCCUPATION. (e.g., CARPENTER)

VAPD(7)	The patient's EMPLOYMENT STATUS in internal^external format. (e.g., 4^SELF EMPLOYED)
VAERR	The error flag will have one of the following values. 0 -- no errors encountered 1 -- error encountered - DFN or ^DPT(DFN,0) is not defined

10. REG^VADPT

Returns REGISTRATION/DISPOSITION data.

Input:	DFN	This required variable is the internal entry number in the PATIENT file.
	VAROOT	This optional variable can be set to a local variable or global name in which to return the output. (e.g., VAROOT="DGADD")
	VARP("F")	Can be defined as the "from" date for which registrations are desired. This must be passed as a valid VA File-Manager date. (e.g., VARP("F")=2930101)
	VARP("T")	Can be defined as the "to" date for which registrations are desired. This must be passed as a valid VA File-Manager date. If neither VARP("F") nor VARP("T") are defined, all registrations will be returned. (e.g., VARP("T")=2930530)
	VARP("C")	Can be defined as the number of registrations you want returned in the array. (e.g., VARP("C")=5 - will return 5 most recent)

Output:	^UTILITY("VARP",\$J,#,"I") Internal format ^UTILITY("VARP",\$J,#,"E") External format Piece 1 Registration Date/Time Piece 2 Status Piece 3 Type of Benefit applied for Piece 4 Facility Applying to Piece 5 Who Registered Piece 6 Log out (disposition) date/time Piece 7 Disposition Type Piece 8 Who Dispositioned
	VAERR The error flag will have one of the following values. 0 -- no errors encountered 1 -- error encountered - DFN or ^DPT(DFN,0) is not defined

11. SDE^VADPT

Returns ACTIVE clinic enrollments for a patient.

Input:	DFN	This required variable is the internal entry number in the PATIENT file.
Output:	^UTILITY("VAEN",\$J,#,"I") Internal format ^UTILITY("VAEN",\$J,#,"E") External format Piece 1 Clinic Enrolled in Piece 2 Enrollment Date Piece 3 OPT or AC	
	VAERR The error flag will have one of the following values. 0 -- no errors encountered 1 -- error encountered - DFN or ^DPT(DFN,0) is not defined	

12. SDA^VADPT

Returns APPOINTMENT DATE/TIME data for a patient.

Input:	DFN	This required variable is the internal entry number in the PATIENT file.
	VASD("T")	Can be defined as the "to" date for which registrations are desired. This must be passed as a valid VA File-Manager date. If neither VASD("F") nor VASD("T") are defined, all future appointments will be returned.
	VASD("F")	Can be defined as the "from" date for which appointments are desired. This must be passed as a valid VA File-Manager date. If not defined, it is assumed only future appointments should be returned.
	VASD("W")	Can be passed as the specific STATUS desired in the following format. If not passed, only those appointments which are still scheduled (or kept in the event of a past date) for both inpatients and outpatients will be returned.

If VASD("W")

<u>Contains a</u>	<u>These appts. are returned</u>
1	Active/Kept
2	Inpatient appts. only
3	No-shows
4	No-shows, auto-rebook
5	Cancelled by Clinic
6	Cancelled by Clinic, auto rebook
7	Cancelled by Patient
8	Cancelled by Patient, auto rebook
9	No action taken

VASD("C",Clinic IFN)

Can be set up to contain only those internal file entries from the HOSPITAL LOCATION file for clinics which you would like to see appointments for this particular patient. You may define this array with just one clinic or with many. If you do not define this variable, it will be assumed that you want appointments for this patient in all clinics returned.

Output:

^UTILITY("VASD",\$J,#,"I") Internal format

^UTILITY("VASD",\$J,#,"E") External format

Piece 1	Date/Time of Appointment
Piece 2	Clinic
Piece 3	Status
Piece 4	Appointment Type

VAERR

The error flag will have one of the following values.

0 -- no errors encountered

1 -- error encountered - DFN or

^DPT(DFN,0) is not defined

13. PID^VADPT

This call is used to obtain the patient identifier in long and brief format.

Input:

DFN

This required variable is the internal entry number in the PATIENT file.

VAPTYP

This optional variable can be set to the internal number of a patient eligibility. The variable can be used to indicate the patient's type such as VA, DOD, or IHS through the eligibility. If this variable is not defined or the eligibility does not exist, the VA patient IDs will be returned.

Output:	VA("PID")	The long patient identifier. (e.g., 111-22-3333P)
	VA("BID")	The short patient identifier. (e.g., 3333P)
	VAERR	The error flag will have one of the following values. 0 -- no errors encountered 1 -- error encountered - DFN or ^DPT(DFN,0) is not defined

14. **PID^VADPT6**

This call returns the same variables as the call mentioned above, but will eliminate the unnecessary processing time required calling PID^VADPT.

15. **ADM^VADPT2**

This returns the internal file number of the admission movement. If VAINDT is not defined, this will use "NOW" for the date/time.

Input:	DFN	This required variable is the internal entry number in the PATIENT file.
	VAINDT	This optional variable may be set to a past date/time for which the programmer wishes to know the patient's inpatient status. This must be passed as an internal VA FileManager date/time format. (e.g., 2880101.08)
Output:	VADMVT	Returns the internal file number of the admission movement.
	VAERR	The error flag will have one of the following values. 0 -- no errors encountered 1 -- error encountered - DFN or ^DPT(DFN,0) is not defined

16. KVAR^VADPT

This call is used to remove all variables defined by the VADPT routine. The programmer should elect to utilize this call to remove the arrays which were returned by VADPT.

17. KVA^VADPT

This call is used as above and will also kill the VA("BID") and VA("PID") variables.

18. COMBINATIONS

The following calls may be made to return a combination of arrays with a single call.

Input: DFN This required variable is the internal entry number in the PATIENT file.

See specific call for other variable input

Output:

CALL	DEMOGRAPHIC	ELIGIBILITY	INPATIENT	INPATIENT	ADDRESS	SERVICE	MONETARY	REGISTRATION	ENROLLMENT	APPOINTMENT
	VADM	VAEL	VAIN	VAIP	VAPA	VASV	VAMB	UTILITY("VARP"	UTILITY("VAEN"	UTILITY("VASD"
OERR	X		X							
1	X		X							
2	X	X								
3		X	X							
4	X				X					
5			X		X					
6	X	X			X					
7		X				X				
8		X				X	X			
9	X							X	X	X
10									X	X
51	X			X						
52		X		X						
53				X	X					
ALL	X	X	X		X	X	X	X	X	X
A5	X	X		X	X	X	X	X	X	X

Alpha Subscripts

Call	Variable	Alpha Translation
------	----------	-------------------

DEM^VADPT	VADM(1)	VADM("NM")
	VADM(2)	VADM("SS")
	VADM(3)	VADM("DB")
	VADM(4)	VADM("AG")
	VADM(5)	VADM("SX")
	VADM(6)	VADM("EX")
	VADM(7)	VADM("RE")
	VADM(8)	VADM("RA")
	VADM(9)	VADM("RP")
	VADM(10)	VADM("MS")

ELIG^VADPT	VAEL(1)	VAEL("EL")
	VAEL(1,#)	VAEL("EL",#)
	VAEL(2)	VAEL("PS")
	VAEL(3)	VAEL("SC")
	VAEL(4)	VAEL("VT")
	VAEL(5)	VAEL("IN")
	VAEL(5,#)	VAEL("IN",#)
	VAEL(6)	VAEL("TY")
	VAEL(7)	VAEL("CN")
	VAEL(8)	VAEL("ES")
	VAEL(9)	VAEL("MT")

MB^VADPT	VAMB(1)	VAMB("AA")
	VAMB(2)	VAMB("HB")
	VAMB(3)	VAMB("SS")
	VAMB(4)	VAMB("PE")
	VAMB(5)	VAMB("MR")
	VAMB(6)	VAMB("SI")
	VAMB(7)	VAMB("DI")
	VAMB(8)	VAMB("OR")
	VAMB(9)	VAMB("GI")

Call	Variable	Alpha Translation
------	----------	-------------------

SVC^VADPT	VASV(1)	VASV("VN")
	VASV(1,#)	VASV("VN",#)
	VASV(2)	VASV("AO")
	VASV(2,#)	VASV("AO",#)
	VASV(3)	VASV("IR")
	VASV(3,#)	VASV("IR",#)
	VASV(4)	VASV("PW")
	VASV(4,#)	VASV("PW",#)
	VASV(5)	VASV("CS")
	VASV(5,#)	VASV("CS",#)
	VASV(6)	VASV("S1")
	VASV(6,#)	VASV("S1",#)
	VASV(7)	VASV("S2")
	VASV(7,#)	VASV("S2",#)
	VASV(8)	VASV("S3")
	VASV(8,#)	VASV("S3",#)
	VASV(9)	VASV("PH")
	VASV(9,#)	VASV("PH",#)

ADD^VADPT	VAPA(1)	VAPA("L1")
	VAPA(2)	VAPA("L2")
	VAPA(3)	VAPA("L3")
	VAPA(4)	VAPA("CI")
	VAPA(5)	VAPA("ST")
	VAPA(6)	VAPA("ZP")
	VAPA(7)	VAPA("CO")
	VAPA(8)	VAPA("PN")
	VAPA(9)	VAPA("TS")
	VAPA(10)	VAPA("TE")
	VAPA(11)	VAPA("Z4")

Call	Variable	Alpha Translation
------	----------	-------------------

OAD^VADPT	VAOA(1)	VAOA("L1")
	VAOA(2)	VAOA("L2")
	VAOA(3)	VAOA("L3")
	VAOA(4)	VAOA("CI")
	VAOA(5)	VAOA("ST")
	VAOA(6)	VAOA("ZP")
	VAOA(7)	VAOA("CO")
	VAOA(8)	VAOA("PN")
	VAOA(9)	VAOA("NM")
	VAOA(10)	VAOA("RE")
	VAOA(11)	VAOA("Z4")

INP^VADPT	VAIN(1)	VAIN("AN")
	VAIN(2)	VAIN("DR")
	VAIN(3)	VAIN("TS")
	VAIN(4)	VAIN("WL")
	VAIN(5)	VAIN("RB")
	VAIN(6)	VAIN("BS")
	VAIN(7)	VAIN("AD")
	VAIN(8)	VAIN("AT")
	VAIN(9)	VAIN("AF")
	VAIN(10)	VAIN("PT")
	VAIN(11)	VAIN("AP")

Call	Variable	Alpha Translation
------	----------	-------------------

IN5^VADPT	VAIP(1)	VAIP("MN")
	VAIP(2)	VAIP("TT")
	VAIP(3)	VAIP("MD")
	VAIP(4)	VAIP("MT")
	VAIP(5)	VAIP("WL")
	VAIP(6)	VAIP("RB")
	VAIP(7)	VAIP("DR")
	VAIP(8)	VAIP("TS")
	VAIP(9)	VAIP("MF")
	VAIP(10)	VAIP("BS")
	VAIP(11)	VAIP("RD")
	VAIP(12)	VAIP("PT")
	VAIP(13)	VAIP("AN")
	VAIP(13,#)	VAIP("AN",#)
	VAIP(14)	VAIP("LN")
	VAIP(14,#)	VAIP("LN",#)
	VAIP(15)	VAIP("PN")
	VAIP(15,#)	VAIP("PT",#)
	VAIP(16)	VAIP("NN")
	VAIP(16,#)	VAIP("NN",#)
	VAIP(17)	VAIP("DN")
	VAIP(17,#)	VAIP("DN",#)
	VAIP(18)	VAIP("AP")

OPD^VADPT	VAPD(1)	VAPD("BC")
	VAPD(2)	VAPD("BS")
	VAPD(3)	VAPD("FN")
	VAPD(4)	VAPD("MN")
	VAPD(5)	VAPD("MM")
	VAPD(6)	VAPD("OC")
	VAPD(7)	VAPD("ES")